| L Number | Hits | Search Text | DB | Time stamp |
|---|---|---|---|---|
| 7 | 224 | ((score$6 tally$6 total$6) with ((route$6 routing) with (each per))) | USPAT | 2004/08/05 17:56 |
| 8 | 56 | (709/(239-241).ccls.) and ((score$6 tally$6 total$6) with ((route$6 routing) with (each per))) | USPAT | 2004/08/05 18:03 |
| 9 | 33 | (709/(239-241).ccls.) and ((score$6 point$6) with ((route$6 routing) with (each per))) | USPAT | 2004/08/05 18:11 |
| 10 | 117 | (route routing) near6 (score scoring) | USPAT | 2004/08/05 18:11 |
| 11 | 2 | ((route routing) near6 (score scoring)) with point | USPAT | 2004/08/05 18:17 |
| 12 | 5 | ((route routing) near12 (score scoring)) with point | USPAT | 2004/08/05 18:15 |
| 13 | 5 | ((route$2 routing) near6 (score$2 scoring)) with point | USPAT | 2004/08/05 18:26 |
| 16 | 2 | ((shortest near6 path) with algo$6) with scor$6 | USPAT | 2004/08/05 18:27 |
| 17 | 486 | ((shortest near6 path) with algo$6) | USPAT | 2004/08/05 18:27 |
| 18 | 297 | ((shortest near6 path) with algo$6) same (tree rout$6) | USPAT | 2004/08/05 18:28 |
| 19 | 8 | (((shortest near6 path) with algo$6) same (tree rout$6)) and scor$6 | USPAT | 2004/08/05 19:06 |
| 20 | 8 | ("3870955" \| "5173689" \| "5235599" \| "5502712" \| "5581689" \| "5590118" \| "5590119" \| "5719854").PN. | USPAT | 2004/08/05 18:32 |
| 21 | 9 | 6282170.URPN. | USPAT | 2004/08/05 18:33 |
| 22 | 1 | 5321815.pn. | USPAT | 2004/08/05 19:06 |
| – | 14 | ((spanning near4 tree$4) with rout$6) and scor$6 | USPAT | 2004/08/04 14:09 |
| – | 0 | ((spanning near4 tree$4) with rout$6) same scoring | USPAT | 2004/07/22 09:37 |
| – | 0 | ((spanning near4 tree$4) with rout$6) same score | USPAT | 2004/07/22 09:37 |
| – | 3 | ((tree$4) with rout$6) same score | USPAT | 2004/07/22 09:43 |
| – | 163 | (minimum near4 rout$6 near4 (cost$6 scor$6)) | USPAT | 2004/07/22 09:44 |
| – | 10 | (minimum near4 rout$6 near4 (cost$6 scor$6)) with tree | USPAT | 2004/07/22 10:04 |
| – | 21 | ingress with egress with tree | USPAT | 2004/07/22 10:07 |
| – | 52409 | 709/(239-241).ccls. | USPAT | 2004/07/22 10:07 |
| – | 67 | (tree with rout$6 with (cost$6 scor$6)) | USPAT | 2004/07/22 10:08 |
| – | 18 | (709/(239-241).ccls.) and ((tree with rout$6 with (cost$6 scor$6))) | USPAT | 2004/07/22 10:12 |
| – | 7 | (node near12 ((select$6 near4 rout$6) with (appear$6 present$6))) | USPAT | 2004/07/22 10:13 |
| – | 8 | (node$6 near12 ((select$6 near4 rout$6) with (appear$6 present$6))) | USPAT | 2004/07/22 10:20 |
| – | 60141 | score scores scoring | USPAT | 2004/07/22 10:26 |
| – | 1931 | (709/(239-241).ccls.) and (score scores scoring) | USPAT | 2004/07/22 10:21 |
| – | 1258 | (tree with (route routing routes)) | USPAT | 2004/07/22 10:22 |
| – | 8 | ((709/(239-241).ccls.) and (score scores scoring)) and ((tree with (route routing routes))) | USPAT | 2004/07/22 10:22 |
| – | 770165 | score scores scoring add adding | USPAT | 2004/07/22 10:27 |
| – | 23375 | (709/(239-241).ccls.) and (score scores scoring add adding) | USPAT | 2004/07/22 10:27 |

BEST AVAILABLE COPY

C:\APPS\EAST\Workspaces\09689902U - Method for designing tree-structured communication routes a

| | | | | |
|---|---|---|---|---|
| – | 230 | ((tree with (route routing routes))) and ((709/(239-241).ccls.) and (score scores scoring add adding)) | USPAT | 2004/07/22 10:50 |
| – | 2 | ("4967345" "5321815").pn. | USPAT | 2004/07/22 10:46 |
| – | 2 | ("4967345" "5321815").pn. and (point$4 scor$6) | USPAT | 2004/07/22 10:46 |
| – | 209 | (((tree with (route routing routes))) and ((709/(239-241).ccls.) and (score scores scoring add adding))) and routing | USPAT | 2004/07/22 10:49 |
| – | 41 | (((tree with (route routing routes))) and ((709/(239-241).ccls.) and (score scores scoring add adding))) and (common near6 node$6) | USPAT | 2004/07/22 10:51 |
| – | 7 | ("4870639" \| "5233604" \| "5999286" \| "6301244" \| "6321271" \| "6347078" \| "6377551").PN. | USPAT | 2004/07/22 10:58 |
| – | 309405 | ((scor$6 point$6) and (rout$6 tree$6)) | USPAT | 2004/08/04 14:10 |
| – | 34810 | ((scor$6 point$6) with (rout$6 tree$6)) | USPAT | 2004/08/04 14:12 |
| – | 29365 | ((scor$6 point$6) with (rout$6)) | USPAT | 2004/08/04 14:12 |
| – | 501 | (((scor$6 point$6) with (rout$6)) same tree) | USPAT | 2004/08/04 14:14 |
| – | 52707 | 709/(239-241).ccls. | USPAT | 2004/08/04 14:13 |
| – | 141 | ((((scor$6 point$6) with (rout$6)) same tree)) and (709/(239-241).ccls.) | USPAT | 2004/08/04 14:13 |
| – | 12 | (((scor$6) with (rout$6)) same tree) | USPAT | 2004/08/04 14:15 |
| – | 3 | (709/(239-241).ccls.) and ((((scor$6) with (rout$6)) same tree)) | USPAT | 2004/08/04 14:14 |
| – | 316 | (((scor$6) with (route$6 routing))) | USPAT | 2004/08/04 14:16 |
| – | 20 | (709/(239-241).ccls.) and ((((scor$6) with (route$6 routing)))) | USPAT | 2004/08/05 16:02 |
| – | 9 | ("5883819" \| "6055571" \| "6308216" \| "6385204" \| "6446122" \| "6466985" \| "6631135" \| "6636516" \| "6647412").PN. | USPAT | 2004/08/05 15:50 |
| – | 18 | (709/(239-241).ccls.) and ((((score$6) with (route$6 routing)))) | USPAT | 2004/08/05 16:03 |
| – | 0 | (709/(239-241).ccls.) and ((score$6) with ((route$6 routing) with (each per))) | USPAT | 2004/08/05 17:57 |
| – | 0 | ((score$6) with ((route$6 routing) with (each per))) | USPAT | 2004/08/05 17:56 |

BEST AVAILABLE COPY

C:\APPS\EAST\Workspaces\09689902U - Method for designing tree-structured communication routes a